

The super strong dripline with excellent uniformity



Product description

Uniflow Pc® is a low density polyethylene dripline characterized by a cylindrical dripper with pressure-compensating flow.

The pressure-compensation mechanism is guaranteed by the silicone membrane which keeps the flow rate constant as the pressure varies.

Product range

DIAMETER Ø - mm	16	20					
THICKNESS mil	4	4					
THICKNESS	1.10						
FLOW RATE* 3,5bar	1,6 - 2,0 - 2,	2 - 4,0 - 4,3					
SPACING cm		0 - 23 - 25 - 30 - 33 0 - 100 - 120 - 150					

Table in nominal values

*≥ 35 mil *< 35 mil minimum pressure 0,5 bar maximum pressure 3,5 bar maximum pressure 3,5 bar

On request:

- Available in brown and white color
- Availability of alternating pitch emitters

Dripper features

- Cylindrical dripper;
- Pressure-compensating flow;
- Labyrinth with self-cleaning design and large water passages;
- Integrated filter reduces the passage of impurities;
- No sensitivity to pressure;
- Low coefficient of technological variation;

Recommended applications

Uniflow Pc® is ideal in the case of steep terrain, with slopes and for long stretches.









Crops

Uniflow Pc® is suitable for open field or greenhouse applications in multi-seasonal tree crops such as oranges, lemons, grapes, apples, pears, almonds, olives, kiwis, hazelnuts.



Advantages

- Perfect emission uniformity;
- Reliable operation and longer life;
- High resistance to UV rays and fertilizers used in agriculture;
- Very little maintenance required.

DRIP IRRIGATION CYLINDRICAL DRIPLINES

Maximum length of recommended lines, in metres, with emission uniformity (E.U.) of 85%

Nominal Diameter Ø 16 mm

THICKNESS	DIAMETER Internal mm	FLOW RATE	↓ SPACING cm										Working pressure
mil			15	20	25	30	33	40	50	60	75	100	(bar)
	13.70		43	58	80	100	118	135	151	166	180	194	1.00
		1,60	64	86	119	148	175	200	223	245	266	287	2.00
			77	103	141	177	210	239	268	294	320	346	3.00
		2,20	36	48	67	84	99	113	126	139	151	163	1.00
44			53	71	99	124	146	167	187	205	223	241	2.00
			63	85	118	147	175	201	223	246	268	288	3.00
		4,30	21	28	39	50	59	67	75	82	89	96	1.00
			31	42	58	73	86	99	110	122	132	143	2.00
			37	50	70	87	104	119	132	146	159	171	3.00

Nominal Diameter 20 mm

THICKNESS	DIAMETER	(I/h)	SPACING cm										Working pressure
mil	Internal mm	FLOW RATE	15	20	25	30	33	40	50	60	75	100	(bar)
			62	83	118	148	175	201	225	248	270	290	1.00
		1,60	92	122	173	217	258	296	332	366	398	430	2.00
			109	146	207	260	309	355	398	439	478	516	3.00
		2,20	52	69	99	124	147	168	188	208	226	243	1.00
44	17.40		77	103	144	182	216	248	279	307	334	360	2.00
			91	122	172	217	259	297	333	367	400	432	3.00
		4,30	31	41	58	73	87	100	112	123	134	145	1.00
			45	61	85	107	128	147	165	182	198	213	2.00
			54	72	101	129	153	176	197	217	237	256	3.00

The values of the lines in meters are indicative



DRIP IRRIGATION CYLINDRICAL DRIPLINES





Specifications Packaging - Standard rolls

	Ö	THICKNIESS	Roll length	Rolls	/ Container-	Truck	Meters /	Container	
DIAMETER Ø - mm	THICKNESS mil	NESS	20Ft	40FtHC	Truck	20Ft	40FtHC	Meters / Truck	
16	44	400	170	400	500	68000	160.000	200.000	

Specifications Packaging - Small rolls

DIAMETER Ø - mm	Ö	Roll length	Rolls / pallets	Rolls	/ Container-	Truck	Meters /	Container		
	THICKNESS mil	m		20Ft	40FtHC	Truck	20Ft	40FtHC	Meters / Truck	
	44	25	100	1.000	2.000	2.200	25.000	50.000	55.000	
16		50	88	880	1.760	1.936	44.000	88.000	96.800	
10		100	48	480	960	1.056	48.000	96.000	105.300	
		200	28	280	560	616	56.000	112.000	123.200	

Soaplast reserves the right to make to its catalogs and products, at any time and without notice, any modifications which, in its unquestionable judgement, it deems convenient for production purposes and/or useful for improving their quality, functionality and performance.

Price tables

Standard rolls for agriculture

	TUICE	/NITCC								SPA	ACING (cm)					also avail	able over	150cm
DIAMETER Ø			15	20	25	30	33	35	40	50	60	70	75	80	90	100	110	125	150
~	mil	mm		PRICE €/m															
16			0,717	0,512	0,445	0,390	0,373	0,364	0,344	0,316	0,297	0,283	0,278	0,273	0,265	0,258	0,253	0,247	0,239
20	44	1,10	-	0,548	0,482	0,435	0,418	0,409	0,389	0,361	0,343	0,330	0,323	0,319	0,310	0,304	0,299	0,292	0,284

Reduced rolls for gardening

	TUIC	ALESS					SPACING (cm)		also ava	ailable over 40cm		
DIAMETER THICKN		INESS	LENGTH ROLL	15	20	25	30	33	35	40		
	mil	mm		PRICE €/m								
			25		0,774	0,659	0,587	0,558	0,542	0,509		
4.4	4.4		50		0,765	0,650	0,578	0,549	0,533	0,500		
16	44	1,10	100		0,699	0,584	0,512	0,483	0,467	0,434		
			200		0,664	0,549	0,477	0,448	0,432	0,399		